



TECHNICAL DATA SHEET

Product: Aropack 403 comp. A

PRODUCT DESCRIPTION

The Isocyanate **Aropack 403 componente A** is a polymeric MDI selected for the production of low density foam aimed to the packaging field.

PRODUCT SPECIFICATIONS AND TYPICAL PROPERTIES

Appearance	: brown liquid
Free NCO content, % wt	: 30 - 32
Specific gravity at 25°C	: 1,23
Viscosity at 25°C, mPa·s	: 150 - 200
Acidity (ppm HCl)	: 200 max
Freezing point, °C	: ≤ 5
Specific heat (Cp), kJ / kg·K	: 1.51 about

STORING AND HANDLING

The isocyanate **Aropack 403 componente A** should be stored in tightly closed containers protected from moisture preferably at 10-30°C in well ventilated dry areas. Minimum storage temperature shall not be lower than 5°C.
Shelf life: 6 months in well closed containers.

HEALTH AND SAFETY ADVICE

The product is irritant to respiratory tract, skin and eyes. During handling, it is recommended to operate in a well ventilated area, to wear protective garments, gloves and goggles for a full eye protection. In case of contact with eyes or skin, wash with plenty of water and ask for medical advice. Exposure to excessive vapour concentrations causes irritation: wear a respirator with organic vapours filter.

Please refer to the Material Safety Data Sheet.

PACKAGING

The isocyanate **Aropack 403 componente A** is supplied in drums of 250 kg and tank trucks.

We do not assume any risk and liability resulting from the product use, either as such and in manufacture processes, use which should anyway be in compliance with the above information. The above technical information is provided for guidance purposes only; we do not assume any liability for the results obtained therefrom, as neither for its utilization.